

REMARKS

In the Office Action, the textual portion of the specification was objected to as being replete with grammatical and idiomatic errors. Claims 4 and 8 were also objected to for various informalities. The Office Action also rejected the pending claims as follows. Claims 1, 5, 6, 8, 9, 10 and 18-21 were rejected under 35 U.S.C. § 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention; and Claims 1-21 were rejected under 35 U.S.C. § 102(e) as being anticipated by U.S. Patent No. 6,684,081 to Sarkkinen et al.

The Specification, the Abstract and Claims 1-10, 11-17 and 20 have been amended. Claims 18, 19 and 21 have been cancelled. No new matter is presented.

In response to the rejections under 35 U.S.C. § 112, second paragraph, the amendments to the Specification and claims

Sarkkinen et al. is cited in the Office Action as anticipating each pending claim. An anticipation rejection requires that a single cited reference disclose each and every recitation of each rejected claim. For at least the following reasons, the rejection must be withdrawn.

In regard to Claim 1, the Examiner states that Sarkkinen et al. allegedly discloses a service announcement message that includes “sending times and sending time duration as parameters.” (Office Action, page 6.) However, neither the cited portion nor elsewhere does Sarkkinen et al. include such disclosure, and Sarkkinen et al. fails to disclose or suggest at least the recitation of wherein said request includes sending times and sending time duration as parameters of Claim 1.

In regard to Claim 10, the Examiner cites Sarkkinen et al. as allegedly disclosing a UTRAN that "arranges time for scheduling." (Office Action, page 15.) However, neither the cited portion nor elsewhere does Sarkkinen et al. include such disclosure, and Sarkkinen et al. fails to disclose or suggest at least the recitation of arranging by the UTRAN of a sending time of a MBMS notification message.

The Examiner further states that "Claim 15 has similar limitations of Claim 10" and rejected Claim 15 "under the same rationale as in Claim 10 above." (Office Action, page 18.) Accordingly, for at least the above reason, the rejection of Claim 15 must be withdrawn.

In regard to Claim 20, the Examiner cites Sarkkinen et al. as allegedly disclosing UTRAN "and the apparatuses in core network co-establish network resources." (Office Action, page 21.) However, contrary to an alleged co-establishing, the invention of Claim 20 *co-releases* network resources, which is not disclosed in Sarkkinen et al.

For at least the above reasons, it is respectfully submitted that all pending claims herein, namely Claims 1-17 and 20, are in condition for allowance. Should the Examiner believe that a telephone conference or personal interview would facilitate resolution of any remaining matters, it is requested that the Examiner contact Applicant's attorney at the below number.

THE FARRELL LAW FIRM
333 Earle Ovington Boulevard, Suite 701
Uniondale, New York 11553
Tel 516-228-3565

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Douglas M. Owens III", written over a horizontal line.

Douglas M. Owens III
Reg. No. 51,314
Attorney for Applicant(s)

Enclosures:

Substitute Specification, with redline; and
Substitute Specification, with redline accepted

~~Using Cell Broadcast for MBMS Service Announcement and~~
~~Notification~~ **USING CELL BROADCAST FOR MBMS SERVICE**
ANNOUNCEMENT AND NOTIFICATION

5

PRIORITY

This application claims priority to an application filed in the Chinese Industrial Property Office on August 15, 2002, assigned Serial No. 02130506.4, as well as to application PCT/KR03/01648 filed August 14, 2003, the contents of which are incorporated herein by reference.

10

Background of the invention

1. Field of invention

15

The present invention relates to a method for sending and receiving Multimedia Broadcast/Multicast Service (MBMS) data in communication system, especially to a method of sending and receiving ~~Service~~ service announcement ~~Announcement~~ and ~~Service~~ service notification in Multimedia Broadcast/Multicast Service with the aid of using cell broadcast.

20

2. Description of the prior art

Multimedia Broadcast/Multicast Service (hereinafter referred to as MBMS) is a new service under standardization by 3rd Generation Partnership Project (hereinafter referred to as 3GPP). The standard being developed is TS23.846, whose latest version is 1.1.1. MBMS service is a unidirectional point-to-multipoint (p-t-m) service, whose most remarkable characteristic is that it can make use of radio resources and network resources efficiently.

A system structure of MBMS is described in the following with reference to Figure 1. As shown in Figure 1, the MBMS network structure is based on the core network of General Packet Radio Service (hereinafter referred to as GPRS), and further adds new network elements. Broadcast and multicast service center 101 (hereinafter referred to as BM-SC) is the service control center of MBMS system. Gateway GPRS Supporting Node 102 (hereinafter referred to as GGSN) and Service GPRS Supporting Node 103 (hereinafter referred to as SGSN) compose the transmission network of MBMS service and provide ~~route~~route-routing for the transmission of data. Home Location Register 106 (hereinafter referred to as HLR) stores the data related to a user and can provide services such as user's authentication. Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network 104 (hereinafter referred to as UTRAN) provides radio resources for MBMS service over the air-interface. Uu107 indicates a radio interface between terminal and access network. User Equipment 105 (hereinafter referred to as UE) is a terminal device for receiving

data. Cell Broadcast Center 108 (hereinafter referred to as CBC) is a data source of cell broadcast. Radio resources used by MBMS service are not dedicated for one user, but are shared by all users using this service.

5 A MBMS multicast service flow is described in the following with reference to Figure 2. As shown in Figure 2, the MBMS multicast service flow includes the following steps:

10 ~~In 200,~~ Subscription step, 200 establishes the relationship between user and service provider, which allows the user to receive the related MBMS multicast service.

15 ~~In 201,~~ Service announcement step, 201 informs UEs about the types and service areas of forthcoming multicast services.

~~In 202,~~ Joining step, 202 is the process by which a subscriber joins a multicast group, i.e. the user registers the network in which the MBMS multicast service types that he is willing to receive.

20 ~~In 203,~~ MBMS multicast mode bearer set up step 203, establishes the network resources for MBMS multicast data transfer.

In ~~204~~, MBMS notification step 204 informs UEs about forthcoming MBMS multicast data transfer.

5 In ~~205~~, Data transfer step 205 indicates the phase when MBMS multicast service data are transferred from the network to the UEs.

In ~~206~~, MBMS multicast mode bearer release step 206, indicates to release the network resources after MBMS service data transfer finishes.

10 In ~~207~~, Leaving step 207, corresponding to 202 joining step, indicates that a subscriber is leaving a service group, i.e. the user no longer wants to receive Multicast mode data of a specific service.

15 The necessary flow of providing a MBMS broadcast service is described with reference to Figure 3. As shown in Figure 3, the MBMS broadcast service flow includes the flowing steps:

~~300~~, Service announcement step 300, which informs UEs about the types and service areas of forthcoming services.

20 ~~301~~, MBMS broadcast mode bearer setup step 301, which establishes the network resources for MBMS broadcast data transfer.

302, MBMS notification step 302, which informs the UEs about the forthcoming MBMS broadcast data transfer.

303, Data transfer step 303, which indicates the phase when MBMS broadcast data are transferred from the network to the UEs.

304, MBMS broadcast mode bearer release step 304, which indicates to release the network resources after MBMS broadcast service data transfer finishes.

In the MBMS Multicast service flow shown in Figure 2, the operation in step 200, 201 and 202 should be performed for different UEs respectively, and remaining steps are performed by all UEs in the same type of service. The series of steps can be performed repeatedly, and step 200, 201, 203, 204 or 207 can be performed in parallel with other steps.

In the MBMS broadcast service flow shown in Figure 3, this series of steps can be performed repeatedly and step 300 and 302 can be performed in parallel with other steps.

A Cell-cell broadcast Broadcast indicates to transfer data transfer by using a common service channel in a cell so as to enable all UEs staying in the

cell capable of receiving the broadcast data of the cell. Refer to 3GPP standard TS25.324 (the latest version is 5.1.0) for the description of cell Broadcast/Multicast Control module BMC.

5 But in the steps shown in Figure 2 and 3, ~~in-existing~~ standard TS23.846, it ~~only mentions mentioned~~ that ~~Service-service~~ announcement steps can be completed by CBC, but the implementation method hasn't been given, and ~~didn't~~ no mention is made of ~~with~~ what devices and how to implement MBMS Service notification steps, ~~which-making make~~ it impossible to completely
10 implement MBMS multicast service flow and MBMS broadcast service flow.

SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a method on
15 how to use a cell broadcast to realize MBMS service announcement and MBMS service notification so as to make MBMS service be a complete flow. It is noted that the Cell Broadcast herein indicates a method of transmitting data via a common service channel over a air-interface of the cell, and it does not relates to specific devices such as CBC. When the cell broadcast is used to support the
20 MBMS service announcement or MBMS service notification, messages sent from CBC and SGSN can all be sent out through cell broadcast.

According to one aspect of the present invention, a process of a UE receiving MBMS multicast service data is shown in Figure 4, and includes the following steps:

5 ~~400~~, Subscription step, 400 indicates a process of the UE subscribing a specific type of MBMS service, which makes the UE establishing relationship with the specific type of MBMS and be authorized to receive this specific type of MBMS service in the future;

10 ~~401~~, Service announcement step, 401 indicates a process of the UE being informed of the MBMS multicast service types and relevant parameters by receiving the service announcement information included in cell broadcast;

15 ~~402~~, Joining step, 402 indicates a process of the UE joining the specific MBMS service multicast group, which corresponds to the MBMS service one to one, the multicast group including all subscribers who receive the MBMS service;

20 ~~403~~, MBMS Service notification step 403, indicates that the UE is informed that the MBMS multicast service data, which is expected to receive by the UE, is forthcoming, by receiving MBMS Service notification information included in cell broadcast;

~~404,~~ __Data transfer step, 404 indicates a process of the UE receiving the MBMS service multicast data;

5 ~~405,~~ __Leaving step, 405 indicates a process of the UE leaving the specific MBMS service multicast group that it is used to join.

 ⊖A process of a UTRAN sending the MBMS multicast service data is shown in Figure 5, and includes the following steps:

10

~~500,~~ __Service announcement step 500, indicates that the UTRAN sends information on MBMS service types and service areas via cell broadcast;

15

~~501,~~ __MBMS multicast mode bearer set up step, 501 indicates a process of co-establishing the network resources for the MBMS service by the UTRAN and a core network;

20

~~502,~~ __MBMS service notification step, 502 indicates that the UTRAN sends a MBMS service notification message via cell broadcast, the message indicating a forthcoming of a specific MBMS service data, and making all users of this multicast group prepare radio resources;

~~503, data~~ Data transfer step 503 indicates that the UTRAN sends a real MBMS service data;

~~504, MBMS multicast mode bearer release step~~ 504, indicates that after the transfer of the MBMS service data being completed, the UTRAN and other devices in the core network co-release the network resources for the MBMS multicast service.

□ A process of the UE receiving the MBMS broadcast service data is shown in Figure 6, and includes the following steps:

~~600, Service announcement step,~~ 600 indicates a process of the UE being informed of the MBMS broadcast service types and relevant parameters by receiving the service announcement information included in the cell broadcast;

~~601, MBMS service notification step,~~ 601 indicates that the UE is informed that the MBMS broadcast service data, which is expected to receive by the UE, is forthcoming, by receiving MBMS service notification information included in cell broadcast;

~~603, Data transfer step~~ 603 indicates a process of the UE receiving the MBMS broadcast service data;

⊖A process of the UTRAN sending the MBMS broadcast service is shown in Figure 7, and includes the following steps:

5 ~~700,~~Service announcement step, 700 indicates that the UTRAN sends information on MBMS service types and service areas via cell broadcast;

~~701,~~MBMS broadcast mode bearer setup step 701; indicates a process of co-establishing the network resources for the MBMS broadcast service by the
10 UTRAN and the core network;

~~702,~~MBMS service notification step, 702 indicates that the UTRAN sends a MBMS service notification message via cell broadcast, the message indicating a forthcoming of a specific MBMS service data, and making all users of this
15 multicast group prepare radio resources;

~~703, data~~Data transfer step, 703, indicates that the UTRAN sends a real MBMS service data;

20 ~~704,~~MBMS broadcast mode bearer release step, 704 indicates that after the transfer of the MBMS service data being completed, the UTRAN and other devices in the core network co-release the network resources for the MBMS

broadcast service.

According to another aspect of the present invention, the method for transferring service announcement of Multimedia Broadcast/Multicast Service (MBMS) includes the following steps:

(a) Broadcast/Multicast Service Center (BM_SC) requests Cell Broadcast Center (CBC) to send a service announcement by a signaling message in a Multimedia Broadcast/Multicast Service (MBMS) service area, wherein said request can include sending times and sending time duration as parameters;

(b) After receiving the signaling message from BM_SC, Cell Broadcast Center (CBC) commands UMTS Terrestrial Radio Access Network (UTRAN) connected with it to send the service announcement through the signaling message;

(c) UMTS Terrestrial Radio Access Network (UTRAN) arranges the sending of Multimedia Broadcast/Multicast Service (MBMS) service announcement message in a prescribed time of one or more schedule periods according to the requirement of Cell Broadcast Center (CBC), adds brief description information to a schedule message for describing each schedule period and sends the schedule message; after receiving the schedule message, UE analyzes the

schedule message and then configures its physical layer to prepare for receiving the Multimedia Broadcast/Multicast Service (MBMS) service announcement message; and

- 5 (d) UMTS Terrestrial Radio Access Network (UTRAN) sends Multimedia Broadcast/Multicast Service (MBMS) service announcement message at the prescribed time₁;

10 Wherein the transfer times in the step (a) can be a plurality of times or infinite times.

In addition, after UMTS Terrestrial Radio Access Network (UTRAN) completes the sending of the Multimedia Broadcast/Multicast Service (MBMS) service announcement message, it may send confirmation information to Cell Broadcast Center (CBC). After receiving the confirmation information from UTRAN, Cell Broadcast Center (CBC) returns confirmation information to BM_SC subsequently.

20 In the above step (b), according to the requirement of BM_SC, Cell Broadcast Center (CBC) can require UMTS Terrestrial Radio Access Network (UTRAN) to send the service announcement periodically a plurality of times or infinite times.

In the above step (d), UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia Broadcast/Multicast Service (MBMS) service announcement message a plurality of times according to the requirement of Cell Broadcast Center (CBC), and the step (c) and (d) can be repeated a plurality of times without a certain precedence order.

In addition, the service announcement message includes parameters of the Multimedia Broadcast/Multicast Service (MBMS) service types and service areas.

According to another aspect of the present invention, the method for transferring a Multimedia Broadcast/Multicast Service (MBMS) service notification includes the following steps:

(a) BM_SC sends the Multimedia Broadcast/Multicast Service (MBMS) data to GGSN;

(b) After receiving said data sent by BM_SC, GGSN sends said data to SGSN by tunneling technique;

(c) After receiving the signals from GGSN, SGSN informs UMTS Terrestrial

Radio Access Network (UTRAN) of the forthcoming of the Multimedia Broadcast/Multicast Service (MBMS) data via a signaling message;

(d) Radio data Access Bearer (RAB) is established between UMTS Terrestrial
5 Radio Access Network (UTRAN) and SGSN;

(e) SGSN sends the Multimedia Broadcast/Multicast Service (MBMS) data to
UMTS Terrestrial Radio Access Network (UTRAN) via Radio data Access
Bearer RAB;

10 (f) After receiving the described data from SGSN, UMTS Terrestrial Radio
Access Network (UTRAN) arranges the sending time of a Multimedia
Broadcast/Multicast Service (MBMS) service notification message, which
includes to arrange sending at the prescribed time of one or more schedule
15 periods, and to add a brief description information to the schedule message for
describing each schedule period and to send the schedule message. After
receiving the schedule message, UE analyzes the schedule message and
configures its physical layer to prepare for receiving the Multimedia
Broadcast/Multicast Service (MBMS) service notification message;

20 (g) UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia
Broadcast/Multicast Service (MBMS) service notification message at the

prescribed time;

(h) UE requests UTRAN to allocate Radio Bearer (RB) via a signaling message, and a plurality of UEs can send requests to UMTS Terrestrial Radio Access Network (UTRAN) simultaneously;

(i) UMTS Terrestrial Radio Access Network (UTRAN) allocates the radio bearer (RB) according to the number of UEs and other comprehensive factors, and informs the UE;

(j) UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia Broadcast/Multicast Service (MBMS) data to the UE via RB.

The above step (e), step (f) and step (g) can be performed without a certain precedence order.

The data transfer flow of MBMS broadcast service is similar with that of multicast service, except that it does not need the step (h), and in the step (i), UMTS Terrestrial Radio Access Network (UTRAN) allocates radio data bearer (RB) according to comprehensive factors without consideration of the number of UEs.

The step of UMTS Terrestrial Radio Access Network (UTRAN) sending a service notification or a service announcement message of Multimedia Broadcast/Multicast Service (MBMS) data via cell broadcast further includes the following steps:

5

(1) Multimedia Broadcast/Multicast Service Control Module (MBMSC) receives a signaling message sent from the core network nodes (SGSN, CBC), which informs UMTS Terrestrial Radio Access Network (UTRAN) to send a service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) and includes the necessary parameters for constructing the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS);

10

(2) Multimedia Broadcast/Multicast Service Control Module (MBMSC) requests Broadcast/Multicast Control protocol (BMC) with a primitive to send the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS), wherein said primitive includes the necessary parameters for constructing the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS);

15

20

(3) BMC constructs the service announcement message or service notification

message of Multimedia Broadcast/Multicast Service (MBMS), saves it in its own sending memory block, and starts up a counter for this message, and the initial value of the counter is equal to the required times for sending the message, and if the message is required to send for infinite times, the initial value of the counter is assigned with zero or negative value;

(4) BMC estimates the transmission rate (V_{need}) needed on the Common Traffic Channel (CTCH) according to all messages currently saved in the sending memory block, wherein said all messages include the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) and other broadcast messages, and if the actual transmission rate (V_{ctch}) on the CTCH is 0, it means that this cell hasn't allocated CTCH resources and it won't continue to send broadcast message, and if the actual transmission rate is much smaller or larger than that needed on the CTCH, BMC reports the actual required transmission rate to Radio Resource Communication (RRC) with a primitive and requests RRC to establish or adjust CTCH resources, during the period of BMC waiting for CTCH resources configured by RRC, if the actual transmission rate does not match with that required and it isn't equal to zero: when the actual transmission rate is much smaller than that required, BMC can still select some messages with high priority and short length to transfer; when the actual transmission rate is much larger than that needed, BMC also reports to RRC, but at this time, resources on CTCH will be wasted;

(5) RRC controls L1 and L2 with a primitive to establish CTCH or adjust CTCH configuration to make CTCH transmission rate match, and RRC informs BMC the new configuration parameters of CTCH with a primitive, and only if the actual transmission rate is not equal to zero, BMC will still continue to send the broadcast message as described in step (4);

(6) BMC adds descriptions for the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) to a pending-for-sending schedule message, and then BMC arranges the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) on a certain position of the schedule period following the schedule message for future sending;

(7) BMC sends the schedule message;

(8) BMC sends the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) at the prescribed time;

(9) After reducing the counter's value by 1, BMC judges: if the value of the counter is negative, it means that the service announcement message or service

notification message of Multimedia Broadcast/Multicast Service (MBMS) is required to send infinite times, then proceeding to step (10) after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step (10) directly; if the value is zero, it means that the times of sending the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) has met the requirement, then BMC returns the confirmation information to Multimedia Broadcast/Multicast Service Control Module (MBMSC) with a primitive and the process of sending service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) is completed;

(10) BMC waits on-timing according to the time interval that the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) is required to send, when the time expires for sending the next service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS), proceeding to step (6).

The step of the UE receiving the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) via cell broadcast further includes the following steps:

(1) Multimedia Broadcast/Multicast Service Control Module (MBMSC) sends a request to BMC with a first primitive for receiving a service announcement message or a service notification message of Multimedia Broadcast/Multicast Service (MBMS);

5

(2) If BMC hasn't received any broadcast message before, proceeding to step (3); otherwise, proceeding to step (9);

(3) BMC informs RRC to receive broadcast message with a second primitive, which includes the parameters that can inform RRC only to receive a BMC preferred message at the prescribed time and to skip some messages;

10

(4) If RRC has not configured CTCH before, RRC configures link layer (L2) and physical layer (L1) to enable UE to receive information on the CTCH and feedbacks necessary CTCH configuration information with a third primitive to BMC at the same time, thereafter proceeding to step (5); if RRC has configured CTCH resources before, proceeding to step (5) directly;

15

(5) According to the requirement of BMC, RRC controls L2 and L1 with a fourth primitive to receive cell broadcast information on the CTCH at the prescribed time;

20

(6) After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message with a fifth primitive;

(7) BMC analyses the received message, and if it is the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS), BMC forwards it to Multimedia Broadcast/Multicast Service Control Module (MBMSC) with a sixth primitive, at the same time the reception is completed; if it is not the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS),
proceeding to step (8);

(8) If the message received by BMC is the schedule message, proceeding to step (9); otherwise, proceeding to step (3);

(9) BMC analyses the schedule message that was received most recently, and checks whether the schedule period described by the schedule message includes the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) or not. If it is positive, proceeding to step (12), otherwise, BMC finds the position of the next schedule message and requests RRC to receive the next schedule message with the second primitive;

(10) RRC controls L1 and L2 to receive the next schedule message at the prescribe time with the fourth primitive;

5 (11) After processing the message received from the CTCH accordingly, L1 and L2 forward the schedule message to BMC with the fifth primitive, and then proceeding to step 9);

10 (12) BMC finds the position of the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message, and requests RRC to receive Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message at the prescribed time with the second primitive;

15 (13) RRC controls L1 and L2 to receive the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message at the prescribed time with the fourth primitive;

20 (14) After processing the message received from the CTCH accordingly, L1 and L2 forward the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message to BMC with the fifth primitive;

(15) BMC forwards the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message to Multimedia Broadcast/Multicast Service (MBMS) with the third primitive and the reception is completed.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will be more apparent from the following detailed description taken in
10 conjunction with the accompanying drawings, in which:

Figure 1 illustrates a diagram of logical network apparatuses that can provide MBMS service;

Figure 2 illustrates a flow of MBMS multicast service;

15 Figure 3 illustrates a flow of MBMS broadcast service;

Figure 4 illustrates a flow of UE receiving MBMS multicast service data;

Figure 5 illustrates a flow of UTRAN sending MBMS multicast service data;

Figure 6 illustrates a flow of UE receiving MBMS broadcast service data;

Figure 7 illustrates a flow of UTRAN sending MBMS broadcast service data;

20 Figure 8 illustrates a message flow of a service announcement process in MBMS service;

Figure 9 illustrates a message flow of a data transfer in MBMS service;

Figure 10 illustrates a functional diagram that explains the process of a service announcement and a service notification in MBMS service; and

Figure 11 illustrates an example of mapping CTCH onto S-CCPCH.

5 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

A message flow of a service announcement process in MBMS multicast service.

In order to explain the process of a service announcement in MBMS service,
10 Figure 8 gives a message flowchart of a service announcement process, which includes the parts of UE receiving and UTRAN sending. The description is as follows:

In Step 801, BM_SC requests CBC to send a service announcement in the
15 service area of MBMS service through a signaling message. This request may include sending times and sending time duration as parameters and the sending times can be infinite times.

In Step 802, CBC commands UTRAN connected with it by a signaling message
20 to send the service announcement; according to the requirement of BM_SC, Cell Broadcast Center (CBC) may require UTRAN to send the service announcement periodically a plurality of times or infinite times.

In Step 803-, UTRAN arranges the time for sending the Multimedia Broadcast/Multicast Service (MBMS) service announcement message in proper time of one or more schedule periods according to the requirement of Cell Broadcast Center (CBC), adds the brief description information to the schedule message that describes each schedule period and sends the schedule message. After receiving the schedule message, UE analyses the schedule message and configures its physical layer to prepare for receiving the Multimedia Broadcast/Multicast Service (MBMS) service announcement message.

In Step 804-, UTRAN sends the MBMS service announcement message at prescribed time. According to the requirement of CBC, the MBMS service announcement message may be sent a plurality of times, and therefore ~~step~~steps 803 and 804 may be repeated a plurality of times without a certain precedence order.

In Step 805-, ~~After~~after the UTRAN completes the sending of the MBMS service announcement message, it sends a confirmation message to CBC.

In Step 806-, ~~After~~after receiving the confirmation message from UTRAN, CBC returns a confirmation message to BM_SC subsequently.

The flow of a MBMS service announcement is the same as that of a MBMS broadcast service.

A transfer process of a MBMS multicast service data including MBMS
5 service notification process.

The function of MBMS service notification is to inform UE the forthcoming MBMS data so that UE can prepare radio resources. Figure 9 is an example of a MBMS data transfer. The function of the MBMS service
10 notification will be explained with reference to the flow of this example:

In Step 901, the BM_SC initiates an MBMS data transfer and sends MBMS data to GGSN.

15 In Step 902, the GGSN sends the data to SGSN by tunneling technique.

In Step 903, the SGSN informs UTRAN about the forthcoming of the MBMS data by a signaling message.

20 In Step 904, a Radio data Access Bearer (hereinafter referred to as RAB) is established between UTRAN and SGSN.

In Step 905, the SGSN sends MBMS data to UTRAN via RAB. Step 905, 906 and 907 are executed without a certain precedence order.

5 In Step 906, UMTS Terrestrial Radio Access Network (UTRAN)
arranges the time for sending the Multimedia Broadcast/Multicast Service
(MBMS) service notification message, which includes to arrange it in proper
time of one or more schedule periods for sending, to add the brief description
information to the schedule message that describes each schedule period and to
send the schedule message; after receiving the schedule message, UE analyses
10 the schedule message and configures its physical layer to prepare for receiving
the MBMS service notification message.

15 In Step 907, UTRAN sends the MBMS service notification message at
the prescribed time.

20 In Step 908, UE requests UTRAN to allocate Radio resources (RB) by a
signaling message. It is possible that there are a plurality of UEs to send requests
to UTRAN simultaneously at this time.

20 In Step 909, UTRAN allocates ~~radio~~ Radio Bearer ~~bearer~~ (hereinafter
referred to as RB) according to the number of UEs and other comprehensive
factors, and informs UE.

In Step 910, UTRAN sends the MBMS data to UE via RB.

The data transfer flow of MBMS broadcast service is similar with that of
5 multicast service, except that it does not need step 908.

⊞A process of UE receiving a MBMS service announcement message

For the UE, the process of receiving a MBMS service announcement
10 message in multicast service and in broadcast service is the same. This process
will be explained in the following with reference to the functional diagram of
Figure 10:

1. When MBMSC (MBMS Service Control module) decides to receive a MBMS
15 service announcement message, MBMSC sends a request to BMC
(Broadcast/Multicast Control protocol) with primitive P'1;

2. If BMC has never received any broadcast message before, proceeding to step
3; otherwise, proceeding to step 9;

20 3. BMC informs RRC to receive the broadcast message with primitive C'1. The
parameters included in C'1 may inform RRC to receive RMC preferred message

only at prescribed time and skip some messages. But in step 3, BMC must require RRC to receive all continuous broadcast messages;

4. If RRC has not configured CTCH before, RRC configures link layer (L2) and physical layer (L1) to enable UE to receive information on the CTCH and feedbacks necessary CTCH configuration information to BMC with primitive C'2 at the same time, then proceeding to step 5; if RRC has configured CTCH resources before, proceeding to step 5 directly;

5. According to the requirement of BMC, RRC controls L2 and L1 with primitive C'3 to receive Cell Broadcast Information on the CTCH at the prescribed time; RRC may control L1 to continuously receive CTCH Block Set (CTCH ~~Block Set~~) or skip some CTCH BSs;

6. After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message (i.e. BMC PDU) with primitive P'3. PDU means Protocol Data Unit, which indicates the message format that BMC can identify and create;

7. BMC analyses the received message. If it is MBMS service announcement message, BMC forwards it with primitive P'2 to MBMSC, at the same time, the reception of this time is completed; otherwise, proceeding to step 8;

8. If the message received by BMC is a schedule message, proceeding to step 9; otherwise, proceeding to step 3;

5 9. BMC analyses the schedule message that was received most recently, and checks whether the schedule period described by the schedule message includes the Multimedia Broadcast/Multicast Service (MBMS) service announcement message. If so, proceeding to step 12; otherwise, BMC finds the position of the next schedule message and requests RRN to receive the next schedule message
10 with primitive C'1;

10. RRC controls L1 and L2 with primitive C'3 to receive the next schedule message at the prescribed time;

15 11. After processing the message received from the CTCH accordingly, L1 and L2 forward the schedule message to BMC with primitive P'3, then proceeding to step 9;

20 12. BMC finds the position of MBMS service announcement message, and requests RRC with primitive C'1 to receive MBMS service announcement message at the prescribed time;

13. RRC controls L1 and L2 with primitive C'3 to receive MBMS service announcement message at the prescribed time;

14. After processing the message received from the CTCH accordingly, L1 and
5 L2 forwards MBMS service announcement message to BMC with primitive P'3;

15. BMC forwards the MBMS service announcement message to MBMS with primitive P'2 and the reception of this time is completed.

10 Notice:

_____ It is noted that a Cell-cell broadcast is transferred through Common Traffic Channel (CTCH), which is a logical channel and is multiplexed with other logical channels into transfer channel FACH together by Medium Access Control sublayer MAC. FACH is then multiplexed together with other transfer
15 channels into physical channel S-CCPCH by physical layer (PHY). An example of CTCH being eventually mapped onto S-CCPCH is shown in Figure 11, in which CTCH is assigned periodically on the S-CCPCH, and this period is called as CTCH Transfer Interval (CTCH TTI). One CTCH BS that includes the whole or part content of Cell Broadcast Message can be transferred in a CTCH TTI.

20

_____ Schedule period is composed of a group of CTCH BSs (from 1 to 255). The introduction of schedule period makes CTCH BSs transferred on the CTCH

be is organized into a continuous schedule period.

□ A process of UTRAN sending MBMS service announcement message

5 _____ For UTRAN, the process of sending MBMS service announcement message in multicast service and in broadcast service is the same. In addition, this process in all cells controlled by the UTRAN is the same also. This process will be explained in the following with reference to the functional diagram of Figure 10 by way of one cell as an example:

10

1. MBMSC receives a signaling message M1 sent from core network node. Here, M1 informs UTRAN to perform the process of MBMS service announcement. M1 includes necessary parameters for MBMS service announcement, such as times for sending MBMS service announcement and the time interval. The core
15 network node that sends M1 signaling message can be SGSN or CBC;

20

2. MBMSC requests BMC with primitive P1 to send MBMS service announcement message. The primitive P1 includes necessary parameters for constructing MBMS service announcement message;

3. After receiving the primitive P1, BMC constructs MBMS service announcement message and saves it in its own sending memory block, and starts

up a counter for this message. The initial value of the counter is equal to the required times of sending message. If the message is required to send for infinite times, the initial value of the counter is assigned with zero or negative value;

5 4. BMC estimates transmission rate (hereinafter referred to as V_{need}) needed on the CTCH according to all messages (including MBMS service announcement messages and other broadcast messages) currently saved in the sending memory block. If the actual transmission rate (hereinafter referred to as V_{ctch}) on the CTCH is 0 (i.e. this cell hasn't allocated CTCH resources) or is much smaller or
10 larger than V_{need} , BMC reports the actually needed transmission rate V_{need} to RRC with primitive C1 and requests RRC to establish or adjust CTCH resources. During the period of BMC waiting for RRC configuring CTCH resources, if V_{ctch} does not match but it isn't equal to zero: when V_{ctch} is smaller than V_{need} , BMC can still select some messages with high priority and short length
15 to transfer; when V_{ctch} is much larger than V_{need} , resources on CTCH can completely meet the need of message transfer, but it will only result in waste. So as described above, BMC still needs to report to RRC;

5. RRC controls L1 and L2 with primitive C3 to establish CTCH or adjust
20 CTCH configuration to make CTCH transmission rate match with V_{need} . RRC informs BMC the new configuration parameters of CTCH with primitive C2. What need to be mentioned is that after BMC receives the primitive C2, whether

CTCH resource adjustment is performed successfully by RRC or not, only if Vetch is not equal to zero, BMC will still continue to send broadcast message as described in step 4;

5 6. BMC adds descriptions for MBMS service announcement message to a pending-for-sending schedule message, and then BMC arranges MBMS service announcement message on a certain position of the schedule period following the schedule message for future sending;

10 7. BMC sends the schedule message with primitive P3;

8. BMC sends MBMS service announcement message at the prescribed time with primitive P3;

15 9. After reducing the counter's value by one, BMC judges: if the value of the counter is negative, it means that MBMS service announcement message is required to send for infinite times, then proceeding to step 10 after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step 10 directly; if the value is zero, it means that the times of sending MBMS service
20 announcement message has reached the requirement, then BMC returns confirmation information to MBMSC with primitive P2 and the process of MBMS service announcement for this time is completed;

10. BMC waits on-timing according to the time interval that MBMS service announcement message is required to send, and when the time expires for sending the next MBMS service announcement message, proceeding to step 6.

5

□A process of UE receiving MBMS service notification message

_____For UE, the process of receiving MBMS service notification message in multicast service and in broadcast service is the same. This process will be explained in the following with reference to the functional diagram of Figure 10:

10

1. When MBMSC (MBMS Service Control module) decides to receive MBMS service notification message, MBMSC sends a request to BMC (Broadcast/Multicast Control protocol) with primitive P'1;

15

2. If BMC has never received any broadcast message before, proceeding to step 3; otherwise, proceeding to step 9;

20

3. BMC informs RRC to receive the broadcast message with primitive C'1. The parameters included in C'1 can inform RRC to receive RMC preferred message only at prescribed time and skip some messages. But in step 3, BMC must require RRC to receive all continuous broadcast messages;

4. If RRC has not configured CTCH before, RRC configures link layer (hereinafter referred to as L2) and physical layer (hereinafter referred to as L1) to enable UE to receive information on the CTCH and feedbacks necessary
5 CTCH configuration information with primitive C'2 to BMC at the same time, thereafter proceeding to step 5; if RRC has configured CTCH resources before, proceeding to step 5 directly;

10 5. According to the requirement of BMC, RRC controls L2 and L1 with primitive C'3 to receive Cell Broadcast Information on the CTCH at the prescribed time; RRC can control L1 to continuously receive CTCH BS or skip some CTCH BSs;

15 6. After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message (i.e. BMC PDU) with primitive P'3. PDU means Protocol Data Unit, which indicates the message format that BMC can identify and create;

20 7. BMC analyses the received message. If it is a MBMS service notification message, BMC forwards it to MBMSC with primitive P'2, at the same time, the reception of this time is completed; otherwise, proceeding to step 8;

8. If the message received by BMC is a schedule message, proceeding to step 9;
otherwise, proceeding to step 3;

9. BMC analyses the schedule message that was received most recently, and
5 checks whether the schedule period described by the schedule message includes
MBMS service notification message. If so, proceeding to step 12; otherwise,
BMC finds the position of the next schedule message and requests RRC to
receive the next schedule message with primitive C'1;

10 10. RRC controls L1 and L2 with primitive C'3 to receive the next schedule
message at the prescribed time;

11. After processing the message received from the CTCH accordingly, L1 and
L2 forwards the schedule message to BMC with primitive P'3 and then
15 proceeding to step 9;

12. BMC finds the position of the MBMS service notification message and
requests RRC with primitive C'1 to receive MBMS service notification message
at prescribed time;

20

13. RRC controls L1 and L2 with primitive C'3 to receive MBMS service
notification message at the prescribed time;

14. After processing the message received from the CTCH accordingly, L1 and L2 forward the MBMS service notification message to BMC with primitive P'3; and

5

15. BMC forwards the MBMS service notification message to MBMSC with primitive P'2 and the reception of this time is completed.

□ A process of UTRAN sending a MBMS service notification message

10

For UTRAN, the process of sending MBMS service notification message in multicast service and in broadcast service is the same. In addition, this process in all cells controlled by the UTRAN is the same also. This process will be explained in the following with reference to the functional diagram of Figure 10 by way of one cell as an example:

15

1. MBMSC receives the signaling message M2 sent from core network node. Here, M2 informs UTRAN to perform the process of MBMS service notification. M2 includes ~~neccessary~~necessary parameters for MBMS service notification, such as times for sending MBMS service announcement and the time interval. The core network node that sends M2 signaling message can be SGSN or CBC;

20

2. MBMSC requests BMC to send MBMS service notification message with primitive P1. The primitive P1 includes necessary parameters for constructing MBMS service notification message;

5 3. After receiving the primitive P1, BMC constructs MBMS service notification message and saves it in its own sending memory block, and starts up a counter for this message. The initial value of the counter is equal to the required times of sending message. If the message is required to send for infinite times, the initial value of the counter is assigned with zero or negative value;

10 4. BMC estimates transmission rate (hereinafter referred to as V_{need}) needed on the CTCH according to all messages (including MBMS service notification messages and other broadcast messages) currently saved in the sending memory block. If the actual transmission rate (hereinafter referred to as V_{ctch}) on the
15 CTCH is 0 (i.e. this cell hasn't allocated CTCH resources) or is much smaller or larger than V_{need} , BMC reports the actually needed transmission rate V_{need} to RRC with primitive C1 and requests RRC to establish or adjust CTCH resources. During the period of BMC waiting for RRC configuring the CTCH resources, if V_{ctch} does not match but it isn't equal to zero: when V_{ctch} is smaller than
20 V_{need} , BMC can still select some messages with high priority and short length to transfer; when V_{ctch} is much larger than V_{need} , resources on CTCH can completely meet the need of message transfer, but it will only result in waste. So

as described in above, BMC still needs to report to RRC;

5. RRC controls L1 and L2 with primitive C3 to establish CTCH or adjust CTCH configuration to make CTCH transmission rate match with Vneed. RRC informs BMC the new configuration parameters of CTCH with primitive C2. It should be noticed that after BMC receives the primitive C2, whether CTCH resource adjustment performed successfully by RRC or not, only if Vctch is not equal to zero, BMC will still continue to send broadcast messages as described in step 4;

6. BMC adds descriptions for MBMS service notification message to a pending-for-sending schedule message, and then BMC arranges MBMS service notification message on a certain position of the schedule period following the schedule message for future sending;

7. BMC sends the schedule message with primitive P3;

8. BMC sends MBMS service notification message at the prescribed time with primitive P3;

9. After reducing the counter's value by one, BMC judges: if the value of the counter is negative, it means that MBMS service notification message is required

to send for infinite times, then proceeding to step 10 after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step 10 directly; if the value is zero, it means that the times of sending MBMS service notification message has met the requirement, then BMC returns confirmation information to MBMSC with primitive P2 and the process of MBMS Service notification for this time is completed; and

10. BMC waits on-timing according to the time interval that MBMS service notification message is required to send. When the time expires for sending the next MBMS service notification message, proceeding to step 6.

Message structures used in the processes of MBMS service announcement and MBMS service notification

Schedule message

A schedule message occupies one or more CTCH BSs included in a schedule period. The schedule message describes the schedule period that directly follows the schedule message to which the schedule message belongs, which makes continuous schedule messages be able to describe continuous schedule periods. Its structure is shown in Table 1.

Information Element (IE)	Need	Plurality existence	Semantics description
Message Type	necessary		
Offset to Begin CTCH BS _{index}	necessary		
Length of Scheduling Period	necessary		
New Message Bitmap	necessary		
Message Description	necessary	1 To <the length of schedule period>	Message description includes a plurality of items, wherein each item describes the message content included in one CTCH BS of the schedule period. The i-th item corresponds to the i-th bit of new message bitmap.

Table 1 structure of schedule message

Message Type, the sub-information element in schedule message, is included in all the cell broadcast message. It describes the message types, whose coding is shown in Table 2.

1	CBS Message
2	Schedule Message
3	CBS41 Message
4	MBMS Service Announcement Message
5	MBMS Service Notification Message
0, 6...255	Reserved for future use (PDU with any coding herein shall be discarded by the protocol of this version.)

Table 2 Coding of Information Element in Schedule Message

New message bitmap, the sub-information element in schedule message, is a map of bits, each bit of which corresponding to a CTCH BS in the schedule period. The bit value is 1, which indicates that CTCH BS includes a new message, and the bit value is 0, which indicates that CTCH BS includes an old message, whose structure is shown in Table 3.

CTCH BS Index B	CTCH BS Index B+1	CTCH BS Index B+2	...					1
								2
								...
	...	CTCH BS Index E-1	CTCH BS Index E	0	0	0	0	n

Table 3 structure of new message bitmap of Information Element in schedule message

10

There is a plurality of sub-information element message descriptions in a schedule message, whose number is equal to the number of CTCH BSs included in the schedule period described by the schedule message. Each CTCH BS is described by one message description, whose structure is shown in Table 4.

15

Information Element (IE)	Need	Type	Semantics description
---------------------------------	------	------	--------------------------

Message Description Type	necessary	Enumerated value (0..255) Table 5	
Message ID	Decision condition MDT11	Enumerated value (0 .. 2 ¹⁶ -1)	
Offset to CTCH BS index of first transmission	Decision condition MDT22	Integer (0..255)	
MBMS service Identity	Decision condition MDT33	IP multicast address	This Information Element is used to identify the types of MBMS service.
MBMS service Identity	Decision condition MDT44	TMGI	This Information Element is used to identify the types of MBMS service.

Table 4 structure of Information Element Message description in schedule message

The types of the message included by CTCH BSs are described by the Sub-
5 information Element Message Description Type of Message Description
Information Element, whose coding is shown in Table 5.

Values	Interpretation
0	Repetition of new BMC message within schedule period
1	New message
2	Reading advised
3	Reading optional
4	Repetition of old BMC message within schedule period
5	Old message
6	Schedule message
7	CBS41 message
8	MBMS service announcement message
9	MBMS service notification message
10. 255	Reserved for future use

Table 5 Coding of the types of Sub-information Element Message Description in Message Description Information Element

5 Since except for Message Description Types, other Sub-information Elements do not absolutely exist, their existence is determined by the decision conditions. The decision condition for each Sub-information existence is shown in Table 6.

Decision condition	Interpretation
MDT11	If Message Description Types = 1 or 5, then: The Information Element of Message Identity exists.
MDT22	If Message Description Types = 0 or 4, then: The Information Element of Offset to CTCH BS index of first transmission exists and indicates the offset of CTCH BS that is the first one including broadcast message in this schedule period to schedule message.
MDT33	If the Message Description Types = 8 (MBMS service announcement message) and the message structure in Table 8 is selected for use, then: The Information Element of MBMS service Identity exists and is identified by IP multicast address;
MDT44	If the Message Description Types = 9 (MBMS service notification message), then: The Information Element of MBMS service Identity exists and is identified by TMGI;

Table 6 Decision Conditions for deciding whether a certain Sub-information Elements exist in Information Element Message Description

◆5 MBMS service announcement message

MBMS service announcement message describes parameters such as MBMS service types and service areas, and may have two kinds of structures: the first kind of structure describes a plurality of MBMS services, as shown in Table 7; and the second kind of structure describes single MBMS service, as shown in Table 8.

10

Information Element (IE)	Need	Semantics description
Message Type	necessary	
Service Number	necessary	The number of MBMS services described in the message
MBMS service Identity 1		The Identity of the first MBMS service: IP multicast address
APN 1		The domain name of access point, for pointing to one GGSN
UE capability 1		The capability of UE required by the first MBMS service
.....		
MBMS service Identity n		The Identity of the n-th MBMS service, n = Service Number
APN n		
UE capability n		The capability of UE required by the n-th MBMS service

Table 7 structure of the first kind of MBMS service announcement message

Information Element (IE)	Need	Semantics description
Message Type	necessary	
MBMS Service Identity		Identity of this MBMS service: IP multicast address
APN		
UE capability		

5 -Table 8 structure of the second kind of MBMS service announcement message

MBMS Service notification message

MBMS service notification message is notification information about a certain forthcoming MBMS service and informs UE to prepare for the MBMS service. Its structure is shown in Table 9.

Information Element (IE)	Need	Semantics description
Message Type	necessary	
MBMS Service Group Identity	necessary	Identity of this MBMS service group: TMGI
QoS QoS	necessary	Quality of Service that can be provided by this MBMS service
Random Mechanism	Optional	Pre-coding random mechanism
Random Value	Optional	
Mask Value	Optional	

Table 9 structure of MBMS service notification message

To avoid the air congestion resulted from simultaneous responses to access network when a plurality of UEs receive MBMS service notification message simultaneously, there should be such a mechanism that allows large number of UEs to respond at different time. Sub-information Element random mechanism, random value and mask value in the MBMS service notification message are all

set for this. Random mechanism indicates which operation mode to be used by coding. IMSI of UE (the unique ID of an UE over the world), random value and mask value are participated in operation together and the operation results is used as time delay that UE initiates a response with time as the unit (e.g. millisecond). Table 10 shows the coding modes of random mechanism.

0	After IMSI modulo the random value, performing bit-by-bit AND operation with the mask value.
1	After IMSI adding to the random value, performing bit-by-bit AND operation with the mask value.
2	After IMSI multiplying with the random value, performing bit-by-bit AND operation with the mask value.
3	After IMSI dividing by the random value, performing bit-by-bit AND operation with the mask value.

Table 10 coding of random mechanism of Sub-information Element in MBMS service notification message

Effects of the invention

~~1-□~~As noted from the above description, the present invention effectively ~~Effectively use~~ uses the network resources; since the processes of MBMS service announcement and service notification are all performed via cell broadcast, the one-to-multiple characteristic of cell broadcast reduces the load of resources resulted from these two processes effectively;

~~2~~ In addition, the present invention effectively ~~Effectively reduce-reduces~~
the standby time of UEs: since cell broadcast enable UEs to receive cell
broadcasts in discontinuous mode, it ~~remarkably~~ remarkably increasing
~~increases~~ the lifetime of UEs' batteries;

5 The present invention also improves scalability ~~Sealability~~: since cell
broadcast uses messages of variable length, it ~~can~~ thereby effectively adding ~~add~~
parameters for future use ~~effectively~~.

ABSTRACT

The present invention proposes a A method of making use of Cell Broadcast to support MBMS transfer service announcement or service notification transfer. The method of transferring service announcement comprises the following includes steps: of a CBC commands commanding a UTRAN connected with it by a signaling message to send a service announcement; the UTRAN arranges the prescribed time of sending the MBMS service announcement message, adds the brief description information to the schedule message and sends the schedule message; after receiving the schedule message, a UE configures a physical layer thereof to prepare for receiving the MBMS service announcement message. ~~UTARN~~ The UTRAN sends MBMS service announcement message at the prescribed time.

USING CELL BROADCAST FOR MBMS SERVICE
ANNOUNCEMENT AND NOTIFICATION

PRIORITY

5 This application claims priority to an application filed in the Chinese
Industrial Property Office on August 15, 2002, assigned Serial No. 02130506.4,
as well as to application PCT/KR03/01648 filed August 14, 2003, the contents of
which are incorporated herein by reference.

10 **Background of the invention**

1. Field of invention

15 The present invention relates to a method for sending and receiving
Multimedia Broadcast/Multicast Service (MBMS) data in communication
system, especially to a method of sending and receiving service announcement
and service notification in Multimedia Broadcast/Multicast Service with the aid
of using cell broadcast.

20 **2. Description of the prior art**

Multimedia Broadcast/Multicast Service (hereinafter referred to as

MBMS) is a new service under standardization by 3rd Generation Partnership Project (hereinafter referred to as 3GPP). The standard being developed is TS23.846, whose latest version is 1.1.1. MBMS service is a unidirectional point-to-multipoint (p-t-m) service, whose most remarkable characteristic is that it can make use of radio resources and network resources efficiently.

A system structure of MBMS is described in the following with reference to Figure 1. As shown in Figure 1, the MBMS network structure is based on the core network of General Packet Radio Service (hereinafter referred to as GPRS), and further adds new network elements. Broadcast and multicast service center 101 (hereinafter referred to as BM-SC) is the service control center of MBMS system. Gateway GPRS Supporting Node 102 (hereinafter referred to as GGSN) and Service GPRS Supporting Node 103 (hereinafter referred to as SGSN) compose the transmission network of MBMS service and provide routing for the transmission of data. Home Location Register 106 (hereinafter referred to as HLR) stores the data related to a user and can provide services such as user's authentication. Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network 104 (hereinafter referred to as UTRAN) provides radio resources for MBMS service over the air-interface. Uu107 indicates a radio interface between terminal and access network. User Equipment 105 (hereinafter referred to as UE) is a terminal device for receiving data. Cell Broadcast Center 108 (hereinafter referred to as CBC) is a data source

of cell broadcast. Radio resources used by MBMS service are not dedicated for one user, but are shared by all users using this service.

A MBMS multicast service flow is described in the following with reference to Figure 2. As shown in Figure 2, the MBMS multicast service flow includes the following steps:

Subscription step 200 establishes the relationship between user and service provider, which allows the user to receive the related MBMS multicast service.

Service announcement step 201 informs UEs about the types and service areas of forthcoming multicast services.

Joining step 202 is the process by which a subscriber joins a multicast group, i.e. the user registers the network in which the MBMS multicast service types that he is willing to receive.

MBMS multicast mode bearer set up step 203 establishes the network resources for MBMS multicast data transfer.

MBMS notification step 204 informs UEs about forthcoming MBMS multicast data transfer.

Data transfer step 205 indicates the phase when MBMS multicast service data are transferred from the network to the UEs.

MBMS multicast mode bearer release step 206 indicates to release the network resources after MBMS service data transfer finishes.

Leaving step 207, corresponding to 202 joining step, indicates that a subscriber is leaving a service group, i.e. the user no longer wants to receive Multicast mode data of a specific service.

The necessary flow of providing a MBMS broadcast service is described with reference to Figure 3. As shown in Figure 3, the MBMS broadcast service flow includes the flowing steps:

Service announcement step 300, which informs UEs about the types and service areas of forthcoming services.

MBMS broadcast mode bearer setup step 301, which establishes the network resources for MBMS broadcast data transfer.

MBMS notification step 302, which informs the UEs about the forthcoming MBMS broadcast data transfer.

Data transfer step 303, which indicates the phase when MBMS broadcast data are transferred from the network to the UEs.

MBMS broadcast mode bearer release step 304, which indicates to release the network resources after MBMS broadcast service data transfer finishes.

In the MBMS Multicast service flow shown in Figure 2, the operation in step 200, 201 and 202 should be performed for different UEs respectively, and remaining steps are performed by all UEs in the same type of service. The series of steps can be performed repeatedly, and step 200, 201, 203, 204 or 207 can be

performed in parallel with other steps.

In the MBMS broadcast service flow shown in Figure 3, this series of steps can be performed repeatedly and step 300 and 302 can be performed in parallel with other steps.

A cell broadcast indicates data transfer by using a common service channel in a cell so as to enable all UEs staying in the cell capable of receiving the broadcast data of the cell. Refer to 3GPP standard TS25.324 (the latest version is 5.1.0) for the description of cell Broadcast/Multicast Control module BMC.

But in the steps shown in Figure 2 and 3, existing standard TS23.846 only mentions that service announcement steps can be completed by CBC, but the implementation method hasn't been given, and no mention is made of what devices and how to implement MBMS Service notification steps, making it impossible to completely implement MBMS multicast service flow and MBMS broadcast service flow.

SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a method on

how to use a cell broadcast to realize MBMS service announcement and MBMS service notification so as to make MBMS service be a complete flow. It is noted that the Cell Broadcast herein indicates a method of transmitting data via a common service channel over a air-interface of the cell, and it does not relates to specific devices such as CBC. When the cell broadcast is used to support the MBMS service announcement or MBMS service notification, messages sent from CBC and SGSN can all be sent out through cell broadcast.

According to one aspect of the present invention, a process of a UE receiving MBMS multicast service data is shown in Figure 4, and includes the following steps:

Subscription step 400 indicates a process of the UE subscribing a specific type of MBMS service, which makes the UE establishing relationship with the specific type of MBMS and be authorized to receive this specific type of MBMS service in the future;

Service announcement step 401 indicates a process of the UE being informed of the MBMS multicast service types and relevant parameters by receiving the service announcement information included in cell broadcast;

Joining step 402 indicates a process of the UE joining the specific

MBMS service multicast group, which corresponds to the MBMS service one to one, the multicast group including all subscribers who receive the MBMS service;

5 MBMS Service notification step 403 indicates that the UE is informed that the MBMS multicast service data, which is expected to receive by the UE, is forthcoming, by receiving MBMS Service notification information included in cell broadcast;

10 Data transfer step 404 indicates a process of the UE receiving the MBMS service multicast data;

Leaving step 405 indicates a process of the UE leaving the specific MBMS service multicast group that it is used to join.

15

A process of a UTRAN sending the MBMS multicast service data is shown in Figure 5, and includes the following steps:

Service announcement step 500 indicates that the UTRAN sends information on MBMS service types and service areas via cell broadcast;

20 MBMS multicast mode bearer set up step 501 indicates a process of co-establishing the network resources for the MBMS service by the UTRAN and a core network;

MBMS service notification step 502 indicates that the UTRAN sends a MBMS service notification message via cell broadcast, the message indicating a forthcoming of a specific MBMS service data, and making all users of this multicast group prepare radio resources;

5 Data transfer step 503 indicates that the UTRAN sends a real MBMS service data;

MBMS multicast mode bearer release step 504 indicates that after the transfer of the MBMS service data being completed, the UTRAN and other devices in the core network co-release the network resources for the MBMS multicast service.

10

A process of the UE receiving the MBMS broadcast service data is shown in Figure 6, and includes the following steps:

Service announcement step 600 indicates a process of the UE being informed of the MBMS broadcast service types and relevant parameters by receiving the service announcement information included in the cell broadcast;

15

MBMS service notification step 601 indicates that the UE is informed that the MBMS broadcast service data, which is expected to receive by the UE, is forthcoming, by receiving MBMS service notification information included in cell broadcast;

20

Data transfer step 603 indicates a process of the UE receiving the MBMS broadcast service data;

A process of the UTRAN sending the MBMS broadcast service is shown in Figure 7, and includes the following steps:

Service announcement step 700 indicates that the UTRAN sends information on MBMS service types and service areas via cell broadcast;

5 MBMS broadcast mode bearer setup step 701 indicates a process of co-establishing the network resources for the MBMS broadcast service by the UTRAN and the core network;

MBMS service notification step 702 indicates that the UTRAN sends a MBMS service notification message via cell broadcast, the message indicating a
10 forthcoming of a specific MBMS service data, and making all users of this multicast group prepare radio resources;

Data transfer step 703, indicates that the UTRAN sends a real MBMS service data;

15 MBMS broadcast mode bearer release step 704 indicates that after the transfer of the MBMS service data being completed, the UTRAN and other devices in the core network co-release the network resources for the MBMS broadcast service.

According to another aspect of the present invention, the method for transferring service announcement of Multimedia Broadcast/Multicast Service (MBMS) includes the following steps:

(a) Broadcast/Multicast Service Center (BM_SC) requests Cell Broadcast Center (CBC) to send a service announcement by a signaling message in a Multimedia

Broadcast/Multicast Service (MBMS) service area, wherein said request can include sending times and sending time duration as parameters;

(b) After receiving the signaling message from BM_SC, Cell Broadcast Center (CBC) commands UMTS Terrestrial Radio Access Network (UTRAN) connected with it to send the service announcement through the signaling message;

(c) UMTS Terrestrial Radio Access Network (UTRAN) arranges the sending of Multimedia Broadcast/Multicast Service (MBMS) service announcement message in a prescribed time of one or more schedule periods according to the requirement of Cell Broadcast Center (CBC), adds brief description information to a schedule message for describing each schedule period and sends the schedule message; after receiving the schedule message, UE analyzes the schedule message and then configures its physical layer to prepare for receiving the Multimedia Broadcast/Multicast Service (MBMS) service announcement message; and

(d) UMTS Terrestrial Radio Access Network (UTRAN) sends Multimedia Broadcast/Multicast Service (MBMS) service announcement message at the prescribed time,

wherein the transfer times in the step (a) can be a plurality of times or infinite times.

In addition, after UMTS Terrestrial Radio Access Network (UTRAN)

completes the sending of the Multimedia Broadcast/Multicast Service (MBMS) service announcement message, it may send confirmation information to Cell Broadcast Center (CBC). After receiving the confirmation information from UTRAN, Cell Broadcast Center (CBC) returns confirmation information to
5 BM_SC subsequently.

In the above step (b), according to the requirement of BM_SC, Cell Broadcast Center (CBC) can require UMTS Terrestrial Radio Access Network (UTRAN) to send the service announcement periodically a plurality of times or
10 infinite times.

In the above step (d), UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia Broadcast/Multicast Service (MBMS) service announcement message a plurality of times according to the requirement of Cell
15 Broadcast Center (CBC), and the step (c) and (d) can be repeated a plurality of times without a certain precedence order.

In addition, the service announcement message includes parameters of the Multimedia Broadcast/Multicast Service (MBMS) service types and service
20 areas.

According to another aspect of the present invention, the method for

transferring a Multimedia Broadcast/Multicast Service (MBMS) service notification includes the following steps:

(a) BM_SC sends the Multimedia Broadcast/Multicast Service (MBMS) data to GGSN;

5 (b) After receiving said data sent by BM_SC, GGSN sends said data to SGSN by tunneling technique;

(c) After receiving the signals from GGSN, SGSN informs UMTS Terrestrial Radio Access Network (UTRAN) of the forthcoming of the Multimedia Broadcast/Multicast Service (MBMS) data via a signaling message;

10 (d) Radio data Access Bearer (RAB) is established between UMTS Terrestrial Radio Access Network (UTRAN) and SGSN;

(e) SGSN sends the Multimedia Broadcast/Multicast Service (MBMS) data to UMTS Terrestrial Radio Access Network (UTRAN) via Radio data Access Bearer RAB;

15 (f) After receiving the described data from SGSN, UMTS Terrestrial Radio Access Network (UTRAN) arranges the sending time of a Multimedia Broadcast/Multicast Service (MBMS) service notification message, which includes to arrange sending at the prescribed time of one or more schedule periods, and to add a brief description information to the schedule message for
20 describing each schedule period and to send the schedule message. After receiving the schedule message, UE analyzes the schedule message and configures its physical layer to prepare for receiving the Multimedia

Broadcast/Multicast Service (MBMS) service notification message;

(g) UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia Broadcast/Multicast Service (MBMS) service notification message at the prescribed time;

5 (h) UE requests UTRAN to allocate Radio Bearer (RB) via a signaling message, and a plurality of UEs can send requests to UMTS Terrestrial Radio Access Network (UTRAN) simultaneously;

(i) UMTS Terrestrial Radio Access Network (UTRAN) allocates the radio bearer (RB) according to the number of UEs and other comprehensive factors, and
10 informs the UE;

(j) UMTS Terrestrial Radio Access Network (UTRAN) sends the Multimedia Broadcast/Multicast Service (MBMS) data to the UE via RB.

The above step (e), step (f) and step (g) can be performed without a
15 certain precedence order.

The data transfer flow of MBMS broadcast service is similar with that of multicast service, except that it does not need the step (h), and in the step (i), UMTS Terrestrial Radio Access Network (UTRAN) allocates radio data bearer
20 (RB) according to comprehensive factors without consideration of the number of UEs.

The step of UMTS Terrestrial Radio Access Network (UTRAN) sending a service notification or a service announcement message of Multimedia Broadcast/Multicast Service (MBMS) data via cell broadcast further includes the following steps:

- 5 (1) Multimedia Broadcast/Multicast Service Control Module (MBMSC) receives a signaling message sent from the core network nodes (SGSN, CBC), which informs UMTS Terrestrial Radio Access Network (UTRAN) to send a service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) and includes the necessary parameters for
10 constructing the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS);
- (2) Multimedia Broadcast/Multicast Service Control Module (MBMSC) requests Broadcast/Multicast Control protocol (BMC) with a primitive to send the service announcement message or service notification message of Multimedia
15 Broadcast/Multicast Service (MBMS), wherein said primitive includes the necessary parameters for constructing the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS);
- (3) BMC constructs the service announcement message or service notification
20 message of Multimedia Broadcast/Multicast Service (MBMS), saves it in its own sending memory block, and starts up a counter for this message, and the initial value of the counter is equal to the required times for sending the message,

and if the message is required to send for infinite times, the initial value of the counter is assigned with zero or negative value;

(4) BMC estimates the transmission rate (V_{need}) needed on the Common Traffic Channel (CTCH) according to all messages currently saved in the sending memory block, wherein said all messages include the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) and other broadcast messages, and if the actual transmission rate (V_{ctch}) on the CTCH is 0, it means that this cell hasn't allocated CTCH resources and it won't continue to send broadcast message, and if the actual transmission rate is much smaller or larger than that needed on the CTCH, BMC reports the actual required transmission rate to Radio Resource Communication (RRC) with a primitive and requests RRC to establish or adjust CTCH resources, during the period of BMC waiting for CTCH resources configured by RRC, if the actual transmission rate does not match with that required and it isn't equal to zero: when the actual transmission rate is much smaller than that required, BMC can still select some messages with high priority and short length to transfer; when the actual transmission rate is much larger than that needed, BMC also reports to RRC, but at this time, resources on CTCH will be wasted;

(5) RRC controls L1 and L2 with a primitive to establish CTCH or adjust CTCH configuration to make CTCH transmission rate match, and RRC informs BMC the new configuration parameters of CTCH with a primitive, and only if the actual transmission rate is not equal to zero, BMC will still continue to send the

broadcast message as described in step (4);

(6) BMC adds descriptions for the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) to a pending-for-sending schedule message, and then BMC arranges the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) on a certain position of the schedule period following the schedule message for future sending;

(7) BMC sends the schedule message;

(8) BMC sends the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) at the prescribed time;

(9) After reducing the counter's value by 1, BMC judges: if the value of the counter is negative, it means that the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) is required to send infinite times, then proceeding to step (10) after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step (10) directly; if the value is zero, it means that the times of sending the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) has met the requirement, then BMC returns the confirmation information to Multimedia Broadcast/Multicast Service Control Module (MBMSC) with a primitive and the process of sending service announcement message or service notification message of Multimedia

Broadcast/Multicast Service (MBMS) is completed;

(10) BMC waits on-timing according to the time interval that the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) is required to send, when the time expires
5 for sending the next service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS), proceeding to step (6).

The step of the UE receiving the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) via cell broadcast further includes the following steps:
10

(1) Multimedia Broadcast/Multicast Service Control Module (MBMSC) sends a request to BMC with a first primitive for receiving a service announcement message or a service notification message of Multimedia Broadcast/Multicast Service (MBMS);

15 (2) If BMC hasn't received any broadcast message before, proceeding to step (3); otherwise, proceeding to step (9);

(3) BMC informs RRC to receive broadcast message with a second primitive, which includes the parameters that can inform RRC only to receive a BMC preferred message at the prescribed time and to skip some messages;

20 (4) If RRC has not configured CTCH before, RRC configures link layer (L2) and physical layer (L1) to enable UE to receive information on the CTCH and feedbacks necessary CTCH configuration information with a third primitive to

BMC at the same time, thereafter proceeding to step (5); if RRC has configured CTCH resources before, proceeding to step (5) directly;

(5) According to the requirement of BMC, RRC controls L2 and L1 with a fourth primitive to receive cell broadcast information on the CTCH at the
5 prescribed time;

(6) After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message with a fifth primitive;

10 (7) BMC analyses the received message, and if it is the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS), BMC forwards it to Multimedia Broadcast/Multicast Service Control Module (MBMSC) with a sixth primitive, at the same time the reception is completed; if it is not the service announcement message or service
15 notification message of Multimedia Broadcast/Multicast Service (MBMS), proceeding to step (8);

(8) If the message received by BMC is the schedule message, proceeding to step (9); otherwise, proceeding to step (3);

20 (9) BMC analyses the schedule message that was received most recently, and checks whether the schedule period described by the schedule message includes

the service announcement message or service notification message of Multimedia Broadcast/Multicast Service (MBMS) or not. If it is positive, proceeding to step (12), otherwise, BMC finds the position of the next schedule message and requests RRC to receive the next schedule message with the second
5 primitive;

(10) RRC controls L1 and L2 to receive the next schedule message at the prescribe time with the fourth primitive;

(11) After processing the message received from the CTCH accordingly, L1 and L2 forward the schedule message to BMC with the fifth primitive, and then
10 proceeding to step 9);

(12) BMC finds the position of the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message, and requests RRC to receive Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message at the prescribed
15 time with the second primitive;

(13) RRC controls L1 and L2 to receive the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message at the prescribed time with the fourth primitive;

(14) After processing the message received from the CTCH accordingly, L1 and
20 L2 forward the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message to BMC with the fifth primitive;

(15) BMC forwards the Multimedia Broadcast/Multicast Service (MBMS) service announcement message or service notification message to Multimedia Broadcast/Multicast Service (MBMS) with the third primitive and the reception is completed.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will be more apparent from the following detailed description taken in conjunction with the accompanying drawings, in which:

10

Figure 1 illustrates a diagram of logical network apparatuses that can provide MBMS service;

Figure 2 illustrates a flow of MBMS multicast service;

Figure 3 illustrates a flow of MBMS broadcast service;

15

Figure 4 illustrates a flow of UE receiving MBMS multicast service data;

Figure 5 illustrates a flow of UTRAN sending MBMS multicast service data;

Figure 6 illustrates a flow of UE receiving MBMS broadcast service data;

Figure 7 illustrates a flow of UTRAN sending MBMS broadcast service data;

Figure 8 illustrates a message flow of a service announcement process in MBMS service;

20

Figure 9 illustrates a message flow of a data transfer in MBMS service;

Figure 10 illustrates a functional diagram that explains the process of a service

announcement and a service notification in MBMS service; and

Figure 11 illustrates an example of mapping CTCH onto S-CCPCH.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5

A message flow of a service announcement process in MBMS multicast service. In order to explain the process of a service announcement in MBMS service, Figure 8 gives a message flowchart of a service announcement process, which includes the parts of UE receiving and UTRAN sending. The description is as follows:

10

In Step 801, BM_SC requests CBC to send a service announcement in the service area of MBMS service through a signaling message. This request may include sending times and sending time duration as parameters and the sending times can be infinite times.

15

In Step 802, CBC commands UTRAN connected with it by a signaling message to send the service announcement; according to the requirement of BM_SC, Cell Broadcast Center (CBC) may require UTRAN to send the service announcement periodically a plurality of times or infinite times.

20

In Step 803, UTRAN arranges the time for sending the Multimedia Broadcast/Multicast Service (MBMS) service announcement message in proper

time of one or more schedule periods according to the requirement of Cell Broadcast Center (CBC), adds the brief description information to the schedule message that describes each schedule period and sends the schedule message. After receiving the schedule message, UE analyses the schedule message and
5 configures its physical layer to prepare for receiving the Multimedia Broadcast/Multicast Service (MBMS) service announcement message.

In Step 804, UTRAN sends the MBMS service announcement message at prescribed time. According to the requirement of CBC, the MBMS service
10 announcement message may be sent a plurality of times, and therefore steps 803 and 804 may be repeated a plurality of times without a certain precedence order.

In Step 805, after the UTRAN completes the sending of the MBMS service announcement message, it sends a confirmation message to CBC.

15 In Step 806, after receiving the confirmation message from UTRAN, CBC returns a confirmation message to BM_SC subsequently.

The flow of a MBMS service announcement is the same as that of a
20 MBMS broadcast service.

A transfer process of a MBMS multicast service data including MBMS

service notification process.

The function of MBMS service notification is to inform UE the forthcoming MBMS data so that UE can prepare radio resources. Figure 9 is an example of a MBMS data transfer. The function of the MBMS service notification will be explained with reference to the flow of this example:

In Step 901, the BM_SC initiates an MBMS data transfer and sends MBMS data to GGSN.

In Step 902, the GGSN sends the data to SGSN by tunneling technique.

In Step 903, the SGSN informs UTRAN about the forthcoming of the MBMS data by a signaling message.

In Step 904, a Radio data Access Bearer (hereinafter referred to as RAB) is established between UTRAN and SGSN.

In Step 905, the SGSN sends MBMS data to UTRAN via RAB. Steps 905, 906 and 907 are executed without a certain precedence order.

In Step 906, UMTS Terrestrial Radio Access Network (UTRAN) arranges the time for sending the Multimedia Broadcast/Multicast Service (MBMS) service notification message, which includes to arrange it in proper time of one or more schedule periods for sending, to add the brief description information to the schedule message that describes each schedule period and to send the schedule message; after receiving the schedule message, UE analyses

the schedule message and configures its physical layer to prepare for receiving the MBMS service notification message.

In Step 907, UTRAN sends the MBMS service notification message at the prescribed time.

5 In Step 908, UE requests UTRAN to allocate Radio resources (RB) by a signaling message. It is possible that there are a plurality of UEs to send requests to UTRAN simultaneously at this time.

In Step 909, UTRAN allocates Radio Bearer (hereinafter referred to as RB) according to the number of UEs and other comprehensive factors, and
10 informs UE.

In Step 910, UTRAN sends the MBMS data to UE via RB.

The data transfer flow of MBMS broadcast service is similar with that of multicast service, except that it does not need step 908.

15

A process of UE receiving a MBMS service announcement message

For the UE, the process of receiving a MBMS service announcement message in multicast service and in broadcast service is the same. This process
20 will be explained in the following with reference to the functional diagram of Figure 10:

1. When MBMSC (MBMS Service Control module) decides to receive a MBMS

service announcement message, MBMSC sends a request to BMC (Broadcast/Multicast Control protocol) with primitive P'1;

2. If BMC has never received any broadcast message before, proceeding to step 3; otherwise, proceeding to step 9;

5 3. BMC informs RRC to receive the broadcast message with primitive C'1. The parameters included in C'1 may inform RRC to receive RMC preferred message only at prescribed time and skip some messages. But in step 3, BMC must require RRC to receive all continuous broadcast messages;

10 4. If RRC has not configured CTCH before, RRC configures link layer (L2) and physical layer (L1) to enable UE to receive information on the CTCH and feedbacks necessary CTCH configuration information to BMC with primitive C'2 at the same time, then proceeding to step 5; if RRC has configured CTCH resources before, proceeding to step 5 directly;

15 5. According to the requirement of BMC, RRC controls L2 and L1 with primitive C'3 to receive Cell Broadcast Information on the CTCH at the prescribed time; RRC may control L1 to continuously receive CTCH Block Set (CTCH BS) or skip some CTCH BSs;

20 6. After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message (i.e. BMC PDU) with primitive P'3. PDU means Protocol Data Unit, which indicates the message format that BMC can identify and create;

7. BMC analyses the received message. If it is MBMS service announcement

message, BMC forwards it with primitive P'2 to MBMSC, at the same time, the reception of this time is completed; otherwise, proceeding to step 8;

8. If the message received by BMC is a schedule message, proceeding to step 9; otherwise, proceeding to step 3;

5 9. BMC analyses the schedule message that was received most recently, and checks whether the schedule period described by the schedule message includes the Multimedia Broadcast/Multicast Service (MBMS) service announcement message. If so, proceeding to step 12; otherwise, BMC finds the position of the next schedule message and requests RRN to receive the next schedule message
10 with primitive C'1;

10. RRC controls L1 and L2 with primitive C'3 to receive the next schedule message at the prescribed time;

11. After processing the message received from the CTCH accordingly, L1 and L2 forward the schedule message to BMC with primitive P'3, then proceeding to
15 step 9;

12. BMC finds the position of MBMS service announcement message, and requests RRC with primitive C'1 to receive MBMS service announcement message at the prescribed time;

13. RRC controls L1 and L2 with primitive C'3 to receive MBMS service
20 announcement message at the prescribed time;

14. After processing the message received from the CTCH accordingly, L1 and L2 forwards MBMS service announcement message to BMC with primitive P'3;

15. BMC forwards the MBMS service announcement message to MBMS with primitive P'2 and the reception of this time is completed.

It is noted that a cell broadcast is transferred through Common Traffic Channel (CTCH), which is a logical channel and is multiplexed with other logical channels into transfer channel FACH together by Medium Access Control sublayer MAC. FACH is then multiplexed together with other transfer channels into physical channel S-CCPCH by physical layer (PHY). An example of CTCH being eventually mapped onto S-CCPCH is shown in Figure 11, in which CTCH is assigned periodically on the S-CCPCH, and this period is called as CTCH Transfer Interval (CTCH TTI). One CTCH BS that includes the whole or part content of Cell Broadcast Message can be transferred in a CTCH TTI.

Schedule period is composed of a group of CTCH BSs (from 1 to 255). The introduction of schedule period makes CTCH BSs transferred on the CTCH is organized into a continuous schedule period.

A process of UTRAN sending MBMS service announcement message

For UTRAN, the process of sending MBMS service announcement message in multicast service and in broadcast service is the same. In addition, this process in all cells controlled by the UTRAN is the same also. This process

will be explained in the following with reference to the functional diagram of Figure 10 by way of one cell as an example:

1. MBMSC receives a signaling message M1 sent from core network node. Here, M1 informs UTRAN to perform the process of MBMS service announcement.
5 M1 includes necessary parameters for MBMS service announcement, such as times for sending MBMS service announcement and the time interval. The core network node that sends M1 signaling message can be SGSN or CBC;

2. MBMSC requests BMC with primitive P1 to send MBMS service announcement message. The primitive P1 includes necessary parameters for
10 constructing MBMS service announcement message;

3. After receiving the primitive P1, BMC constructs MBMS service announcement message and saves it in its own sending memory block, and starts up a counter for this message. The initial value of the counter is equal to the required times of sending message. If the message is required to send for infinite
15 times, the initial value of the counter is assigned with zero or negative value;

4. BMC estimates transmission rate (hereinafter referred to as V_{need}) needed on the CTCH according to all messages (including MBMS service announcement messages and other broadcast messages) currently saved in the sending memory block. If the actual transmission rate (hereinafter referred to as V_{ctch}) on the
20 CTCH is 0 (i.e. this cell hasn't allocated CTCH resources) or is much smaller or larger than V_{need} , BMC reports the actually needed transmission rate V_{need} to RRC with primitive C1 and requests RRC to establish or adjust CTCH resources.

During the period of BMC waiting for RRC configuring CTCH resources, if Vctch does not match but it isn't equal to zero: when Vctch is smaller than Vneed, BMC can still select some messages with high priority and short length to transfer; when Vctch is much larger than Vneed, resources on CTCH can completely meet the need of message transfer, but it will only result in waste. So as described above, BMC still needs to report to RRC;

5. RRC controls L1 and L2 with primitive C3 to establish CTCH or adjust CTCH configuration to make CTCH transmission rate match with Vneed. RRC informs BMC the new configuration parameters of CTCH with primitive C2.

What need to be mentioned is that after BMC receives the primitive C2, whether CTCH resource adjustment is performed successfully by RRC or not, only if Vctch is not equal to zero, BMC will still continue to send broadcast message as described in step 4;

6. BMC adds descriptions for MBMS service announcement message to a pending-for-sending schedule message, and then BMC arranges MBMS service announcement message on a certain position of the schedule period following the schedule message for future sending;

7. BMC sends the schedule message with primitive P3;

8. BMC sends MBMS service announcement message at the prescribed time with primitive P3;

9. After reducing the counter's value by one, BMC judges: if the value of the counter is negative, it means that MBMS service announcement message is

required to send for infinite times, then proceeding to step 10 after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step 10 directly; if the value is zero, it means that the times of sending MBMS service announcement message has reached the requirement, then BMC returns
5 confirmation information to MBMSC with primitive P2 and the process of MBMS service announcement for this time is completed;

10. BMC waits on-timing according to the time interval that MBMS service announcement message is required to send, and when the time expires for sending the next MBMS service announcement message, proceeding to step 6.

10

A process of UE receiving MBMS service notification message

For UE, the process of receiving MBMS service notification message in multicast service and in broadcast service is the same. This process will be
15 explained in the following with reference to the functional diagram of Figure 10:

1. When MBMSC (MBMS Service Control module) decides to receive MBMS service notification message, MBMSC sends a request to BMC (Broadcast/Multicast Control protocol) with primitive P'1;

2. If BMC has never received any broadcast message before, proceeding to step
20 3; otherwise, proceeding to step 9;

3. BMC informs RRC to receive the broadcast message with primitive C'1. The parameters included in C'1 can inform RRC to receive RMC preferred message

only at prescribed time and skip some messages. But in step 3, BMC must require RRC to receive all continuous broadcast messages;

4. If RRC has not configured CTCH before, RRC configures link layer (hereinafter referred to as L2) and physical layer (hereinafter referred to as L1)

5 to enable UE to receive information on the CTCH and feedbacks necessary CTCH configuration information with primitive C'2 to BMC at the same time, thereafter proceeding to step 5; if RRC has configured CTCH resources before, proceeding to step 5 directly;

10 5. According to the requirement of BMC, RRC controls L2 and L1 with primitive C'3 to receive Cell Broadcast Information on the CTCH at the prescribed time; RRC can control L1 to continuously receive CTCH BS or skip some CTCH BSs;

15 6. After processing the data frame received from the CTCH accordingly, L1 and L2 submit it to BMC in the format of BMC message (i.e. BMC PDU) with primitive P'3. PDU means Protocol Data Unit, which indicates the message format that BMC can identify and create;

7. BMC analyses the received message. If it is a MBMS service notification message, BMC forwards it to MBMSC with primitive P'2, at the same time, the reception of this time is completed; otherwise, proceeding to step 8;

20 8. If the message received by BMC is a schedule message, proceeding to step 9; otherwise, proceeding to step 3;

9. BMC analyses the schedule message that was received most recently, and

checks whether the schedule period described by the schedule message includes MBMS service notification message. If so, proceeding to step 12; otherwise, BMC finds the position of the next schedule message and requests RRC to receive the next schedule message with primitive C'1;

5 10. RRC controls L1 and L2 with primitive C'3 to receive the next schedule message at the prescribed time;

11. After processing the message received from the CTCH accordingly, L1 and L2 forwards the schedule message to BMC with primitive P'3 and then proceeding to step 9;

10 12. BMC finds the position of the MBMS service notification message and requests RRC with primitive C'1 to receive MBMS service notification message at prescribed time;

13. RRC controls L1 and L2 with primitive C'3 to receive MBMS service notification message at the prescribed time;

15 14. After processing the message received from the CTCH accordingly, L1 and L2 forward the MBMS service notification message to BMC with primitive P'3; and

15. BMC forwards the MBMS service notification message to MBMSC with primitive P'2 and the reception of this time is completed.

20

A process of UTRAN sending a MBMS service notification message

For UTRAN, the process of sending MBMS service notification message in multicast service and in broadcast service is the same. In addition, this process in all cells controlled by the UTRAN is the same also. This process will be explained in the following with reference to the functional diagram of Figure 10 by way of one cell as an example:

1. MBMSC receives the signaling message M2 sent from core network node. Here, M2 informs UTRAN to perform the process of MBMS service notification. M2 includes necessary parameters for MBMS service notification, such as times for sending MBMS service announcement and the time interval. The core network node that sends M2 signaling message can be SGSN or CBC;

2. MBMSC requests BMC to send MBMS service notification message with primitive P1. The primitive P1 includes necessary parameters for constructing MBMS service notification message;

3. After receiving the primitive P1, BMC constructs MBMS service notification message and saves it in its own sending memory block, and starts up a counter for this message. The initial value of the counter is equal to the required times of sending message. If the message is required to send for infinite times, the initial value of the counter is assigned with zero or negative value;

4. BMC estimates transmission rate (hereinafter referred to as V_{need}) needed on the CTCH according to all messages (including MBMS service notification messages and other broadcast messages) currently saved in the sending memory

block. If the actual transmission rate (hereinafter referred to as V_{ctch}) on the CTCH is 0 (i.e. this cell hasn't allocated CTCH resources) or is much smaller or larger than V_{need} , BMC reports the actually needed transmission rate V_{need} to RRC with primitive C1 and requests RRC to establish or adjust CTCH resources.

5 During the period of BMC waiting for RRC configuring the CTCH resources, if V_{ctch} does not match but it isn't equal to zero: when V_{ctch} is smaller than V_{need} , BMC can still select some messages with high priority and short length to transfer; when V_{ctch} is much larger than V_{need} , resources on CTCH can completely meet the need of message transfer, but it will only result in waste. So
10 as described in above, BMC still needs to report to RRC;

5. RRC controls L1 and L2 with primitive C3 to establish CTCH or adjust CTCH configuration to make CTCH transmission rate match with V_{need} . RRC informs BMC the new configuration parameters of CTCH with primitive C2. It should be noticed that after BMC receives the primitive C2, whether CTCH
15 resource adjustment performed successfully by RRC or not, only if V_{ctch} is not equal to zero, BMC will still continue to send broadcast messages as described in step 4;

6. BMC adds descriptions for MBMS service notification message to a pending-for-sending schedule message, and then BMC arranges MBMS service
20 notification message on a certain position of the schedule period following the schedule message for future sending;

7. BMC sends the schedule message with primitive P3;

8. BMC sends MBMS service notification message at the prescribed time with primitive P3;

9. After reducing the counter's value by one, BMC judges: if the value of the counter is negative, it means that MBMS service notification message is required

5 to send for infinite times, then proceeding to step 10 after adding 1 to the value of the counter; if the value of the counter is positive, proceeding to step 10 directly; if the value is zero, it means that the times of sending MBMS service notification message has met the requirement, then BMC returns confirmation information to MBMSC with primitive P2 and the process of MBMS Service
10 notification for this time is completed; and

10. BMC waits on-timing according to the time interval that MBMS service notification message is required to send. When the time expires for sending the next MBMS service notification message, proceeding to step 6.

15 Message structures used in the processes of MBMS service announcement and MBMS service notification

◆ Schedule message

20 A schedule message occupies one or more CTCH BSs included in a schedule period. The schedule message describes the schedule period that directly follows the schedule message to which the schedule message belongs,

which makes continuous schedule messages be able to describe continuous schedule periods. Its structure is shown in Table 1.

Information Element (IE)	Need	Plurality existence	Semantics description
Message Type	necessary		
Offset to Begin CTCH BS _{index}	necessary		
Length of Scheduling Period	necessary		
New Message Bitmap	necessary		
Message Description	necessary	1 To <the length of schedule period>	Message description includes a plurality of items, wherein each item describes the message content included in one CTCH BS of the schedule period. The i-th item corresponds to the i-th bit of new message bitmap.

Table 1 structure of schedule message

5

Message Type, the sub-information element in schedule message, is included in all the cell broadcast message. It describes the message types, whose coding is shown in Table 2.

1	CBS Message
2	Schedule Message
3	CBS41 Message
4	MBMS Service Announcement Message
5	MBMS Service Notification Message
0, 6...255	Reserved for future use (PDU with any coding herein shall be discarded by the protocol of this version.)

Table 2 Coding of Information Element in Schedule Message

New message bitmap, the sub-information element in schedule message, is a map of bits, each bit of which corresponding to a CTCH BS in the schedule period. The bit value is 1, which indicates that CTCH BS includes a new message, and the bit value is 0, which indicates that CTCH BS includes an old message, whose structure is shown in Table 3.

CTCH BS Index B	CTCH BS Index B+1	CTCH BS Index B+2	...					1
								2
								...
	...	CTCH BS Index E-1	CTCH BS Index E	0	0	0	0	n

Table 3 structure of new message bitmap of Information Element in schedule message

There is a plurality of sub-information element message descriptions in a

schedule message, whose number is equal to the number of CTCH BSs included in the schedule period described by the schedule message. Each CTCH BS is described by one message description, whose structure is shown in Table 4.

Information Element (IE)	Need	Type	Semantics description
Message Description Type	necessary	Enumerated value (0..255) Table 5	
Message ID	Decision condition MDT11	Enumerated value (0 .. 2 ¹⁶ -1)	
Offset to CTCH BS index of first transmission	Decision condition MDT22	Integer (0..255)	
MBMS service Identity	Decision condition MDT33	IP multicast address	This Information Element is used to identify the types of MBMS service.
MBMS service Identity	Decision condition MDT44	TMGI	This Information Element is used to identify the types of MBMS service.

5 **Table 4 structure of Information Element Message description in schedule message**

The types of the message included by CTCH BSs are described by the Sub-information Element Message Description Type of Message Description Information Element, whose coding is shown in Table 5.

10

Values	Interpretation
0	Repetition of new BMC message within schedule period
1	New message
2	Reading advised
3	Reading optional
4	Repetition of old BMC message within schedule period
5	Old message
6	Schedule message
7	CBS41 message
8	MBMS service announcement message
9	MBMS service notification message
10. 255	Reserved for future use

Table 5 Coding of the types of Sub-information Element Message Description in Message Description Information Element

- 5 Since except for Message Description Types, other Sub-information Elements do not absolutely exist, their existence is determined by the decision conditions. The decision condition for each Sub-information existence is shown in Table 6.

Decision condition	Interpretation
MDT11	If Message Description Types = 1 or 5, then: The Information Element of Message Identity exists.
MDT22	If Message Description Types = 0 or 4, then: The Information Element of Offset to CTCH BS index of first transmission exists and indicates the offset of CTCH BS that is the first one including broadcast message in this schedule period to schedule message.
MDT33	If the Message Description Types = 8 (MBMS service announcement message) and the message structure in Table 8 is selected for use, then: The Information Element of MBMS service Identity exists and is identified by IP multicast address;
MDT44	If the Message Description Types = 9 (MBMS service notification message), then: The Information Element of MBMS service Identity exists and is identified by TMGI;

Table 6 Decision Conditions for deciding whether a certain Sub-information Elements exist in Information Element Message Description

◆5 MBMS service announcement message

MBMS service announcement message describes parameters such as MBMS service types and service areas, and may have two kinds of structures: the first kind of structure describes a plurality of MBMS services, as shown in Table 7; and the second kind of structure describes single MBMS service, as shown in Table 8.

10

Information Element (IE)	Need	Semantics description
Message Type	necessary	
Service Number	necessary	The number of MBMS services described in the message
MBMS service Identity 1		The Identity of the first MBMS service: IP multicast address
APN 1		The domain name of access point, for pointing to one GGSN
UE capability 1		The capability of UE required by the first MBMS service
.....		
MBMS service Identity n		The Identity of the n-th MBMS service, n = Service Number
APN n		
UE capability n		The capability of UE required by the n-th MBMS service

Table 7 structure of the first kind of MBMS service announcement message

Information Element (IE)	Need	Semantics description
Message Type	necessary	
MBMS Service Identity		Identity of this MBMS service: IP multicast address
APN		
UE capability		

5 Table 8 structure of the second kind of MBMS service announcement message

MBMS Service notification message

MBMS service notification message is notification information about a certain forthcoming MBMS service and informs UE to prepare for the MBMS service. Its structure is shown in Table 9.

Information Element (IE)	Need	Semantics description
Message Type	necessary	
MBMS Service Group Identity	necessary	Identity of this MBMS service group: TMGI
QoS	necessary	Quality of Service that can be provided by this MBMS service
Random Mechanism	Optional	Pre-coding random mechanism
Random Value	Optional	
Mask Value	Optional	

Table 9 structure of MBMS service notification message

To avoid air congestion from simultaneous responses to access network when a plurality of UEs receive MBMS service notification message simultaneously, there should be such a mechanism that allows large number of UEs to respond at different time. Sub-information Element random mechanism, random value and mask value in the MBMS service notification message are all set for this. Random mechanism indicates which operation mode to be used by coding. IMSI of UE (the unique ID of an UE over the world), random value and

mask value are participated in operation together and the operation results is used as time delay that UE initiates a response with time as the unit (e.g. millisecond). Table 10 shows the coding modes of random mechanism.

0	After IMSI modulo the random value, performing bit-by-bit AND operation with the mask value.
1	After IMSI adding to the random value, performing bit-by-bit AND operation with the mask value.
2	After IMSI multiplying with the random value, performing bit-by-bit AND operation with the mask value.
3	After IMSI dividing by the random value, performing bit-by-bit AND operation with the mask value.

5 **Table 10 coding of random mechanism of Sub-information Element in MBMS service notification message**

As noted from the above description, the present invention effectively uses the network resources since the processes of MBMS service announcement and service notification are all performed via cell broadcast, the one-to-multiple
10 characteristic of cell broadcast reduces the load of resources resulted from these two processes effectively.

In addition, the present invention effectively reduces standby time of UEs since cell broadcast enable UEs to receive cell broadcasts in discontinuous mode,
15 remarkably increasing the lifetime of UEs' batteries;

The present invention also improves scalability since cell broadcast uses messages of variable length, thereby effectively adding parameters for future use.

ABSTRACT

A method of making use of Cell Broadcast to support MBMS transfer service announcement or service notification transfer. The method of transferring service announcement includes steps of a CBC commanding a UTRAN
5 connected with it by a signaling message to send a service announcement; the UTRAN arranges the prescribed time of sending the MBMS service announcement message, adds the brief description information to the schedule message and sends the schedule message; after receiving the schedule message, a UE configures a physical layer thereof to prepare for receiving the MBMS
10 service announcement message. The UTRAN sends MBMS service announcement message at the prescribed time.